

537, 112

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 June 2004 (17.06.2004)


PCT

(10) International Publication Number
WO 2004/051995 A2

- (51) International Patent Classification⁷: **H04N 5/74**
- (21) International Application Number:
PCT/US2003/038011
- (22) International Filing Date:
26 November 2003 (26.11.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/430,996 4 December 2002 (04.12.2002) US
- (71) Applicant (for all designated States except US): **THOMSON LICENSING S. A.** [FR/FR]; 46 Quai A. Le Gallo, F-92648 Boulogne Cedex (FR).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **DRAZIC, Valter** [FR/FR]; 7 Allee du Pigeon Blanc, F-35830 Betton (FR). **SARAYEDDINE, Khaled** [FR/FR]; 12 rue du douaire, F-35410 Nouvoitou (FR). **HALL, Estill, Thone, Jr.** [US/US]; 9978 Niagara Drive, Fishers, IN 46038 (US). **O'DONNELL, Eugene, Murphy** [US/US]; 7594 Timber Springs Drive, Fishers, IN 46038 (US).
- (74) Agents: **TRIPOLI, Joseph, S. et al.**; Thomson Licensing Inc., 2 Independence Way, Suite #2, Princeton, NJ 08540 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: TWO-STAGE PROJECTION ARCHITECTURE



(57) Abstract: A two-stage light projection system is provided for projecting an image comprising a matrix of light pixels having modulated luminance. A first imager is configured to modulate a light band on a pixel-by-pixel basis proportional to gray scale values provided for each pixel of the image to provide a first output matrix. A second imager is positioned and configured to receive the first output matrix and modulate the individual modulated pixels of light from the first imager on a pixel-by-pixel basis proportional to a second gray scale value provided for each pixel. A relay lens system having a single-gauss lens set and a mirror positioned at the system stop focuses the modulated light output from the first imager on a pixel-by-pixel basis onto the corresponding pixels of the second imager.

WO 2004/051995 A2



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.